

UHF Windshield tag

Long range UHF windshield tag

Key Features:

- Identification up to 4 meters [12 ft]
- Passive battery free tags
- Thin, flexible sticker format
- Protection against harmful UV rays
- Optional break upon removal
- Customised printing
- Security protected
- EPC Gen 2 compatible

The UHF Windshield Tag is a passive UHF transponder offering long range identification up to 4 meters [12 ft.]. The UHF Windshield Tag offers cost effective long range vehicle identification for parking applications.

The UHF windshield tag is an effective solution for upgrade of existing proximity installations for parking. It offer long range within reach, it was never so affordable.

The UHF windshield tag is based on passive UHF technology. The tag does not contain a battery and is maintenance free.

The UHF Windshield tag is featured with an excellent adhesive to allow quick and easy installation inside the vehicle to the windshield. The thin, flexible, UHF sticker format is easy to install and offers a tamperproof AVI solution by way of permanently affixing it to the windshield. The tag is protected against harmful UV rays.

Break upon removal

For added security, tamperproof UHF windshield tags are also available. These tags will damage and break upon removal, ensuring they will no longer operate.



Security

The UHF windshield tags are available in various formats ensuring compatibility to any installation. Wiegand and magstripe formatted tags are available to complement any access application. Nedap XS formatted tags are available to ensure easy integration for existing TRANSIT Standard of Entry users. Nedap formatted UHF windshield tag are featured with special security protection to provide data integrity and to prevent copying.

Customisation

The tag lay-out can be customized allowing you to promote your company with a tag that shows off your company name or logo.

Optional the tag ID number can be printed on the UHF windshield tag in barcode 39 format. The barcode can be read by means of a barcode scanner to offer easy enrollment of tags into a management system and efficient enforcement of vehicles.

Applications

Typical applications include vehicle access to car parks, gated communities/ condominiums, offices etc.

Change without prior notice/ version 1.4_English

Specifications



UHF Windshield Tag

Operating frequency	850 - 950 MHz
Standard	EPC Gen 2
Dimensions	101.6 x 25.4 x 0.9 mm [4 x 1 x 0.04 in]
Protection	IP54 [approx. NEMA 2]
Colour	White with printing
Material	Polyester
Operating temperature	-20 ... +70°C [-4 ... +158°F]
Detection range	4 meters [12 ft] with TRANSIT UHF reader, when applied on glass*
Humidity	10% ... 93% relative humidity, non condensing
Customisation	Customised tag printing on request. Optional Barcode 39 printed on the tag on request
Identification	R/O Read only number
Tag Formats	Wiegand Magstripe Nedap XS format (compatible to Nedap's AVI tag format)
Mounting	Onto the windshield, the tag is featured with a standard pressure-sensitive adhesive back
Part numbers	9942327 UHF Windshield Tag 9942335 UHF Windshield Tag Tamperproof (break upon removal)
Documentation	UHF Windshield Tag_InstallGuide_English

**depending on glass in m (ft) and reader and environment*

Represented by:

NEDAP N.V. Automatic Vehicle Identification - PO Box 103 - NL-7140 AC Groenlo
T: +31 (0) 544 471 666 - F: +31 (0) 544 464 255 - E: info-avi@nedap.com

www.nedapavi.com